


CMED

120V, 220V-230V and 277V

LED Ceiling Flush Mounted Luminaires



Catalog #		Type
Project		Date
Prepared by		

Flush Mount LED



* Puff-Square



CMED 111 (114, 116)

* Puff-Mushroom



CMED 211 (214, 216, 218)

* Puff-Drum



CMED 211F (214F, 216F)

FEATURES and FUNCTIONS

- 120V AC LED module with integrated IC chip imbed on board and 10-100% Triac dimming with most of leading and trailing edge dimmer switches in the market.
- Hard gauge metal back plate and the heat sink to facilitate heat dissipation.
- Acylic plastic diffused lens delivers perfect light distribution.
- 90CRI Standard. Available in 2700K, 3000K, 3500K, 4000K and 5000K.
- Triac dimmable standard.

Listing

- CSA-us Certificated
- State of california Title 24
- Energy star Approved & Listed
- Damp location

Warranty

- 5years of lamp life.

SPECIFICATION

HOUSING	CMED 111	CMED 114	CMED 116	CMED 211	CMED 214	CMED 216	CMED 218	CMED 211F	CMED 214F	CMED 216F
Shade Diameter x Assembled Height(H)	10.7"(Square) x 2-7/8"	14.5"(Square) x 3-1/8"	16.5"(Square) x 3-9/16"	11.7"(Ø) x 3-7/8"	14.1"(Ø) x 4"	16.5"(Ø) x 4-7/16"	18"(Ø) x 4-13/16"	11"(Ø) x 3-3/8"	13.2"(Ø) x 3-1/2"	14.6"(Ø) x 3-11/16"
Wattage (Typ)	15W	23W	34W	15W	23W	34W	34W	15W	23W	34W
Lumen (Typ)	950	1,300	2,000	950	1,300	2,000	2,000	950	1,300	2,000
Efficacy (LPW)	63 lm/W	57 lm/W	59 lm/W	63 lm/W	57 lm/W	59 lm/W	59 lm/W	63 lm/W	57 lm/W	59 lm/W
C R I (Typical)	80, 90									
Color (+/-5%)	2700K, 3000K, 3500K, 4000K, 5000K									
Dimming	Triac(Consult with factory for approved dimmers)									

ORDERING INFORMATION

Housing	Watts	CRI	CCT	Diffuser	Finish
CMED 1XX 11", 14", 16"	15 15W	8 80	27 2700K	P Plastic	WH White
CMED 2XX 11", 14", 16", 18"	23 23W	9 90	30 3000K		
CMED 2XXF 11", 14", 16"	34 34W		35 3500K		
			40 4000K		
			50 5000K		

*Consult with factory for custom finishes

Example : CMED 114-23-830-P-WH

- - - -