

High Watt Commercial

DLED-196H

9" NON-IC, Architectural Frame-in Kit

Max. 84W LED, 120V-277V Input



Catalog #		Type
Project		Date
Prepared by		



9" LED Architectural Frame-in Kit



TML-199RLS
Open Reflector



TML-190BLS
Baffle w/ Reflector



TML-196BLS
Baffle w/ Regressed Lens




TML-196RLS
Reflector w/ Regressed Lens



TML-198LS
Reflector w/ Frosted Floating Lens

* All trims are rated for damp location, and regressed lens trims are for wet location listed.
* Wide beam reflector is standard. Also available in other beam in reflector.(consult with factory)

LINE DRAWING



Height : 10-1/2" (variable)
Ceiling Cut-out : 9-3/4"
Overlap Trim : 10-9/16"

DESCRIPTION

9" Architectural frame-in kits combined with LED module and integral reflector. This is designed for use in non-insulated ceiling. Insulation material must be kept a minimum of 3" from fixture. Provided in high efficacy LED with dimmable driver and the special optical diffusion allows high lumen transmission and light uniformity.

Listing

- cUL Listed
- State of California Title 24
- Energy star Approved & Listed

Warranty

- 5 years of lamp life.

SPECIFICATION

LED Quantity	1EA (COB)			
Input Voltage	120V-277V AC ^{*(80Ra / 4000K)}			
Wattage (Typ)	50 W	63 W	75 W	84 W
Lumen (Typ)	4,500	5,670	6,750	7,560
Efficacy (LPW)	90 lm/W	90 lm/W	90 lm/W	90 lm/W
Beam Angle	55°			
CRI (Typical)	80, 90			
Color (+/-5%)	2700K, 3000K, 4000K, 5000K			
Dimming	Triac & 0-10V the both (Consult with factory for approved dimmers)			

FEATURES and FUNCTIONS

- Galvanized steel construction.
- 20-gauge CRS mounting ring, black-painted. 1-5/8" deep collar may use for various thickness of ceiling materials.
- Aluminum extruded Heat sink designed to facilitate heat dissipation
- Heavy gauge aluminum reflector anodized in clear, haze, gold, champagne and pewter color finish.
- (5) 1/2" knockouts with true pry-out slots and (4) knockouts with Romex cable clamp.
- Commercial mounting kit provided up to 5" vertical adjustment, which accommodates 1/2" EMT conduit, optional HB-24 or HBC-24 bar hanger or lathing channels for T-bar grid or concealed spline ceiling.
- 120V~277V 60Hz Triac and 0-10V dimmable driver for most dimmers in the market.

ORDERING INFORMATION

Housing	Watts	CRI	CCT	Beam Angle	Driver	Trim	Reflector Finish	Baffle Finish	Optional Metal Trim Ring Finish
DLED-196H 9", Non-IC, Architectural Frame-in Downlight Kit	50 50W	8 80	27 2700K	N Narrow	UTD 120V, Triac Dimming (Standard)	TML-199RLS	HC Haze Clear	WH White	WH White
	63 63W	9 90	30 3000K	M Medium		TML-190BLS	WH White	BK Black	BK Black
	75 75W		40 4000K	W Wide	UZTD 120~277V, 0-10V Dimming	TML-196BLS			
	84 84W		50 5000K	WW Wide+		TML-196RLS			
							TML-198LS		
*Option - EM=Emergency battery backup						*Consult with factory for custom finishes			

Example : DLED-196H-50-830-W-UTD

- - - -

Example : TML-199RLS-HC-WH

- -