


LVN Series

120V ~ 277V

LED Vapor Tight Linear Fixture



Catalog #		Type
Project		Date
Prepared by		


LED



LVNS




LVNW



Dimension Table

Housing	[LVNS2-20]	[LVNS4-35]
L (Length)	24-3/8" (620mm)	46-1/2" (1,180mm)

[LVNS]



Dimension Table

Housing	[LVNW2-20]	[LVNW4-35]
L (Length)	25-7/8" (656mm)	49-1/2" (1,256mm)

[LVNW]

DESCRIPTION

A cost effective and energy efficient alternative to fluorescents, the LED vapor Lock Fixture, features a full-length, gasketed polycarbonate lens and single piece non-corrosive (PC) Polycarbonate body. Designed to meet or exceed IP65 ratings against dust and pressurized water jets. Ideal for use as utility lighting in parking garage and stairwells, in tunnels or hallways, or anywhere meeting applicable building and safety codes. Effective advanced AC module in low profile and driverless along easy installation and cost effective.

SPECIFICATION

HOUSING	LVNS2-20	LVNS4-35	LVNW2-20	LVNW4-35
Wattage (Typ)	20W	35W	20W	35W
Lumen (Typ)	1,800	3,150	1,800	3,150
Efficacy (LPW)	90 lm/W	90 lm/W	90 lm/W	90 lm/W
CRI (Typical)	80			
Color (+/-5%)	4000K, 5000K, 5700K			
Dimming	Triac and 0-10V the both			

FEATURES and FUNCTIONS

- Single piece polycarbonate body and gasketed polycarbonate lens.
- IP65 rated against ingress of dust and water jets from all directions.
- 120V~277V AC LED module with integrated IC chip imbed on board.
- Microwave motion sensor available.
- 0-10V dimming standard.
- Operating Temperature: -22°F to 122°F
- Surface mount with two removable, snap-in mounting brackets.

Listing

- CSA-us Certificated
- State of California Title 24
- DLC qualified
- Wet location(IP65)

Warranty

- 5years of lamp life.

ORDERING INFORMATION

* Consult with factory for approved dimmers

Housing	CRI	CCT	Finish
LVNS2-20 2', 20W	80	40 4000K	WH White
LVNS4-35 4', 35W		50 5000K	
LVNW2-20 2', 20W	57 5700K		
LVNW4-35 4', 35W			

*Consult with factory for custom finishes

Example : LVNS2-20-840-WH

- -