



Spotstar Miniature
120V, 220V-230V and 277V
LED Track Head Track Lighting



Catalog #		Type
Project		Date
Prepared by		

Track LED

LED Track Lighting



Dimension Table

Housing	[STS-2200]	[STS-2300]	[STS-2400]
Head D (Diameter)	2-1/8" (Ø55mm)	2-5/8" (Ø68mm)	3-1/2" (Ø87.5mm)
H (Height)	5-1/8" (130mm)	5-7/8" (150mm)	6-1/4" (160mm)

DESCRIPTION

Spotstar Miniature offers superior output in a small, sleek design allowing spot beam to each object. Designed for optimized optical and thermal management in a slender diecast housing.

FEATURES and FUNCTIONS

- One piece casted aluminum and heat sink designed to facilitate heat dissipation.
- Exchangeable reflector for beam angle, 25 and 40 degree.
- 120V~277V AC LED module integrated IC chip imbed on board.
- Triac dimming is standard.
- Directionally adjustable up to 90° tilt and 355° rotation to shot spotlight into multiple directions.
- Major adaptors provided is compatible with Juno style track, and available with Halo, Capri, Lightolier style adaptors.

Listing

- CSA-us Certificated
- State of California Title 24
- Energy star Approved & Listed

Warranty

- 5years of lamp life.

SPECIFICATION

HOUSING	STS-2200		STS-2300			STS-2400		
Wattage (Typ)	10W	15W	15W	20W	30W	15W	20W	30W
Lumen (Typ)	600	907	975	1,304	1,950	870	1,160	1,732
Efficacy (LPW)	60 lm/W	60.5 lm/W	65 lm/W	65 lm/W	65 lm/W	58 lm/W	58 lm/W	58 lm/W
Beam Angle	25° / 40°							
C R I (Typical)	80							
Color (+/-5%)	2700K, 3000K, 3500K, 4000K, 5000K							
Dimming	Triac & 0-10V the both(Consult with factory for approved dimmers)							

ORDERING INFORMATION

Housing	Watts	CRI	CCT	Beam Angle	Connector Type	Finish
STS-2200	10 10W	8 80	27 2700K	25 25°	J Juno H Halo C Capri L Lightolier G Global	WH White BK Black
STS-2300	15 15W		30 3000K	40 40°		
STS-2400	20 20W		35 3500K			
	30 30W		40 4000K			
			50 5000K			

*Consult with factory for custom finishes

Example : STS-2200-10-830-25-J-BK

- - - - -