


# TMD Series

120V, 220V-230V and 277V

4" IC Rated Downlight with off-board junction box




Catalog #		Type
Project		Date
Prepared by		



## 4" LED



### LINE DRAWING



Ceiling Cut-out : 5"

### SPECIFICATION

Input Voltage	120V and 277V AC	
Wattage (Typ)	10W	
Lumen (Typ)	888 (80CRI)	776 (90CRI)
Efficacy (LPW)	88.8 lm/W	77.6 lm/W
Compatible Housing	See Housing Compatibility section	
CRI (Typical)	80, 90	
Color (+/-5%)	2700K, 3000K, 4000K, 5000K	
Dimming	Triac or 0-10V	

### DESCRIPTION

The 4" TMD Series Downlight screw base for the 4" IC/Airtight and Non-IC incandescent recessed downlight and GU24 adapter for CFL housing. It's designed for use with most 4" housings classified.

#### Listing

- cCSA-us Certificated
- Energy star Approved & Listed
- Wet location (for TML-24B, 24R, 215)
- State of California Title 24
- Damp location

#### Warranty

- 5 years of lamp life.

### FEATURES and FUNCTION

- One piece light engine with durable heat sink and LED allowing for installation to different trim piece exchangeable.
- Easy installation with hinge, off-board j-box.
- Beam changeable optic glass.
- Spring-loaded retention tabs holds downlight snug to ceiling surface.
- 120V AC LED module with integrated IC chip imbed on board.
- Triac dimmable standard.

### ORDERING INFORMATION

\* Consult with factory for approved dimmers

Housing	CRI	CCT	Beam Angle	Trim	Reflector Finish	Baffle Finish	Metal Trim Ring Finish
TMD 4", 10W	8 80	27 2700K	N Narrow	TML-24B Baffle	HC Haze Clear	WH White	WH White
	9 90	30 3000K	W Wide	TML-24R Reflector	WH White	BK Black	BK Black
		40 4000K		TML-28 Gimbal			
		50 5000K		TML-84E Eyeball			
				TML-215 Lens	*for TML-24R	*for TML-24B	

\*Consult with factory for custom finishes

Example : TMD-830-W

□ - □ - □

Example : TML-24B-WH

□ - □