

IC-8068R

120V Line Voltage

6" IC Type Adjustable Remodel Housing For Super Sloped Ceiling

Catalog #		Type
Project		Date
Prepared by		

INCANDESCENT



DESCRIPTION

IC remodel housing designed for sloped ceiling installations in ceilings with a 7/12 to 12/12 pitch. The socket aiming mechanism allows the lamp to be aimed straight down regardless of ceiling pitch.

APPLICATION

The IC-8068R is designed for insulated ceilings and can be in direct contact with Insulation material.

DESIGN FEATURES

• Housing

- Single wall aluminum housing.
- 7-1/4" height allows use in 2"X8" or 2" X10" joist construction.
- Housing adjusts for ceilings up to 1/2" thick.

• Junction Box

- Listed for through branch circuit wiring. (Max. 8 No 12 AWG 90°C branch circuit conductors. (4 in, 4 out)
- (5) 1/2" knockouts with true pry-out slots and (4) knockouts with Romex cable clamp.
- Ground wire provided on J-box.

• Remodel Clips

- 3 remodel clips secure housing and accommodates 1/2" and 5/8" ceiling materials.

• Socket

- Medium base porcelain with nickel-plated copper screw shell.
- Adjustable to position lamp perpendicular to floor.

• Lamp

- Lamp ratings based on trim selected - See trim page for more details.

• Thermal Protector

- Self-resetting thermal protector in the housing deactivates fixture if overheating occurs due to improper lamping or insulation.

Oval Ceiling Cut-out : 8-3/16" x 6-1/2"
Lamp, Max, Watt. : 75W PAR30 / PAR38 / R30

• Optional "Quick Connect" Push-in wire connectors.

- Three "Quick Connectors"
- Pre-installed push-in wire connectors for fast and easy wiring.

